

**HUSTLER**  
*Turf Equipment*

# ATZ

the Hustler All-Terrain Z





THE **ATZ** FROM HUSTLER TURF EQUIPMENT

**Warranties with teeth:** lifetime on the leading edge of the deck, lifetime on the tractor frame, three years on the blade-spindle bearings, three years on the front caster fork bearings and...two years bumper-to-bumper parts and labor

# BORN TO CLIMB

**Any which way you want to go.**

The ATZ™ is first, last, and always a Hustler. And so, while its slope performance represents a 60% improvement over typical Zs, the ATZ™ will deliver all the quality of cut, all the finished appearance for which Hustler Zs are rightly known. Take the ATZ™ up top; it will leave behind none of the standards of design and manufacture that have made Hustler Super Zs the preferred choice of knowledgeable landscape professionals nationwide.



All the benefits of the most productive Z-rider on the market. Now, with no fear of heights.



Certified 2-post ROPS with 4-post roll cage for sure, comfortable operator security.

Oil cooler and fan with spoiler

Deluxe suspension seat with seat belt for added security, added operator comfort

Dual cup holders, the largest of any Z in the world

Patented automatic parking brake system


12.2 gallons of fuel capacity, for all-day mowing

Foot-operated deck-lift system


Hydraulic hoses and fittings guaranteed to never leak

White RC 26 wheel motors for more torque at lower pressures, a key ingredient of improved slope performance (Meanwhile, these lower pressures will extend the longevity of pumps and motors.)

60 or 72-inch deck



BUILT-IN UTILITY BAY



EASY SERVICE ACCESS



# SAFER ON SLOPES

**Everything changes at high altitudes. The ATZ™ does too.**

Take the ATZ™ to the top of the steepest hill on your job list. Strap in. Proceed confidently across the slope and notice, as the ATZ™ leans into its work, all the specialized traits of a mower built for diagonal grass.

For jobs on extremely steep slopes, HUSTLER offers the 6400 Hillsider™. The ultimate steep slope mower.



# THE HUSTLER **ATZ** SPECIFICATIONS

## ENGINE

<b>Model</b>	Kohler
<b>Horsepower</b>	27
<b>No. of Cylinders</b>	2
<b>Displacement</b>	44.0 cu in (725 cc)
<b>Compression Ratio</b>	9.0:1
<b>Max. Torque</b>	42.7 ft lbs @ 3000 rpm

**Starter** 12-volt (.8 kw), solenoid shift, positive engagement

**Ignition** Electronic

**Charging System** 12-volt, 15-amp

**Fuel** Unleaded gasoline, octane rating of 87 or higher

**Fuel Filter** Replaceable, automotive-type

**Air Filter** Heavy-duty air cleaner to extend the service interval for excessive, dirty applications and improved performance

**Cooling** Air cooled. Fly-wheel fan

**Governor** Mechanical

## TRACTION DRIVE SYSTEM

**Type** Dual hydrostatic. Individual pumps power two direct-drive wheel motors. Hydrostatic system operates on 10W40 motor oil. Transmission drive (oil) cooler for increased system life.

**Pumps** Two variable displacement, axial-piston type. Each Hydro-Gear BDP21 pump powers one drive-wheel motor.

**Pump Drive** V-belt drive from engine crankshaft

**Final Drive** Direct-drive, high-torque wheel motors. One White RC 26 motor for each drive wheel.

**Filter** 25 micron, spin-on type

**Ground Speed** Infinitely variable:  
0-9 mph (0-14.48 kph) forward  
0-5 mph (0-8.05 kph) reverse

**Steering** Twin-lever steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and turns are all controlled with hand-operated controls

**Turning Radius** True zero degree. Turns within its own length. Counter-rotating, independent drive wheels

**Brakes** Service: Hydrostatic dynamic braking. Parking: Automotive-style drum brakes. When steering levers are placed in neutral position, integral park brakes are automatically engaged

**Mower Drive** Single V-belt drive from engine with electric clutch. Spring tension idler for extended belt life.

**Tires** Front: 13 x 6.50 - 6, NHS semi-pneumatic, smooth Drive: 24 x 12 - 12, Carlisle AT101 ATV bar-tread

## Capacities

Fuel System: 12.2 US gal (46.18 l)  
Hydraulic Oil: 2 US gal (7.57 l)

**Dimensions** Height: 71 in (180.34 cm)

## W/60 in Deck

Length: 87 in (221 cm)  
Overall width: 62 in (157.48 cm) w/discharge chute up  
Tire-to-tire width: 59 in (149.86 cm)  
Weight: 1500 lbs (680.25 kg)

## W/72 in Deck

Length: 87 in (221 cm)  
Overall width: 70.5 in (179.07 cm) w/discharge chute up  
Tire-to-tire width: 59 in (149.86 cm)  
Weight: 1540 lbs (698.39 kg)

**Safety Features** Operator presence system connected to deck and drive clutches. Stabilizer rollers at rear of tractor. Seat belt. Certified ROPs with 4-post roll cage

**Seat** Molded-vinyl, suspension seat with armrests and seat belt. Fore and aft adjustment

**Construction** Mainframe is 1.5 in x 3 in x .187 in (3.8 cm x 7.62 cm x .47 cm) rectangular steel tubing. Drive motors mounted to .179 in (.45 cm) welded steel. Front caster wheels mounted with roller bearings on each wheel. Front caster forks are .5 in (1.27 cm) steel

**Deck Lift** Foot-operated deck height adjustment. Pin for setting height, detent for transport position

**Controls** Hand-operated choke/throttle, ignition switch, electric mower clutch. Integrated parking brakes

**Indicators** Hour meter, engine warning light

**Cup Holder** Two cup holders molded into the left side fuel tank. Accommodates nearly any cup size including Big Gulp™

**Warranty** Two year, bumper-to-bumper parts and labor Lifetime warranty on tractor frame Lifetime warranty on leading edge of the deck Hydraulic hoses and fittings guaranteed to never leak 3-year warranty on front-caster fork bearings 3-year warranty on blade-spindle bearings

## ATTACHMENTS

### 60" and 72" Side-Discharge Decks

**Type** Free-floating mower using three blades with center blade to the front. Mower is suspended at the corners. Includes 6 deck-mounted rollers to improve flotation in rolling and uneven terrain.

**Deck Lift** Raise and lower deck from driver's seat with simple foot-operated deck-height adjustment. Pin for setting height. Transport position. Change cutting heights, hop curbs and trailer more easily.

**Construction** 125 in (.317 cm) welded steel. Solid 1 in x .375 in (2.55 cm x .95 cm) steel bars reinforce impact areas on trim edges. .187 in x .375 in (.47 cm x .95 cm) in box-section reinforced front edge. Reinforcements welded onto spindle-mount areas. Steel deck housing is 5 in (12.70 cm) deep for high-capacity mowing.

**Cutting Heights** Foot-operated deck height adjustment. Pin for setting height, detent for transport position. Height adjustment in .25 in increments from 1 in to 5 in (2.55 cm to 12.7 cm).

**Mowing Blades** Heavy-duty, high-lift, heat-treated steel  
60 in: 21 in x 3.00 in x .25 in  
72 in: 24 in x 3.00 in x .25 in

## Blade Tip Speed

60 in: 18,350 fpm  
72 in: 18,800 fpm

**Blade Drive** V-belt drive to all three spindles. Spring tension idler pulleys

**Spindles** Machine ductile housing, 1 in (2.5 cm) diameter high carbon steel shafts and sealed ball bearings

**Flotation** Suspended mower floats on four spring-assisted chains. 6 anti-scalp wheels are standard

**Discharge Chute** Over-center design allows for chute to be folded up for improved trailering or to pass thru gates, etc

## Width of Cut

60 in: 60 in (152.4 cm)  
72 in: 69 in (175.26 cm)

## Trim Capacity (left side)

60 in: 3.5 in (8.89 cm)  
72 in: 8 in (20.32 cm)

## ACCESSORIES

**Mulch Kit** Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.

*Specifications subject to change without notice.*

*Hustler has many State Contracts and our GSA Contract Number is GS07F-8756D*

Call us at 1-800-395-4757, or visit us online at [www.hustlerturfequipment.com](http://www.hustlerturfequipment.com)

**HUSTLER**<sup>®</sup>  
*Turf Equipment*



# WHERE NO Z HAS GONE BEFORE

It lives to traverse. A modified Hustler Super Z<sup>®</sup>, the ATZ<sup>™</sup> refuses to slip down, much less back down from 25-degree slopes. It's the perfect addition to a fleet where matchless performance on slopes must involve no compromise with flat-out Z-rider productivity. So say good-bye to wrestling walk-behinds on ground angling more than, say, 10 or 15 degrees. The Hustler ATZ<sup>™</sup> is ready to ride.



- A smooth top speed of 9 mph
- Heavier frame construction and an extra-wide stance of 59" for improved traction and balance
- Wheel weights and added frame weight for increased balance and traction
- Extra length (at 87") for enhanced performance in backing up hills
- 24 x 12--12 Carlisle AT101 ATV bar-tread tires for grab-a-hold traction and sure, steady going (The tires are mounted backwards for even more holding power while backing up hill.)
- 13 x 6.50 Carlisle Reliance semi--pneumatic front caster tires -- no flats, ever!
- 29" seat height, lowest in the industry, making gravity your friend

***The ATZ<sup>™</sup> is waiting to mow where no Z has gone before.***

