



*Professional Mowing Comes Home...™*

# The Mini FasTrak™



*...now in a more compact size and price.*



*Mowers shown with optional armrests.*



***Lifetime Warranty on the tractor frame and leading edge of deck - welded steel. Not stamped! Twin-lever SmoothTrak™ steering with patented automatic park brake system. No maintenance between oil changes. Sealed bearings and commercial-quality blade spindles for trouble-free performance. Very high blade-tip speed for awesome quality of cut. 36" or 42" side-discharge/mulching decks.***





# Mini FasTrak™ 36/42 Specifications

## Engine

Model	Honda	Kohler	Kohler
Horsepower	16	15	17
No. of Cylinders	2	1	1
Displacement	32.3 cu in (530 cc)	29.1 cu in (477 cc)	32.6 cu in (535 cc)
Compression Ratio	8:1	8.5:1	8.5:1
Max. Torque	26.9 ft lbs @ 2500 rpm	25.0 ft lbs @ 2600 rpm	27.9 ft lbs @ 2600 rpm
Models Available	16/36, 16/42	15/36	17/42

**H BEST WARRANTY IN THE BUSINESS**

- A 2-year bumper-to-bumper warranty – parts and labor!
- Lifetime warranty on tractor frame
- Lifetime warranty on the leading edge of the deck
- 3-year warranty on the blade spindle bearings
- 3-year warranty on the front caster fork bearings

Electrical System	12-volt, 15-amp regulated	
Ignition	Electronic	
Fuel Capacity	6 US gal (22.71 l) Site line in fuel tanks	
Transmission	Dual hydrostatic. Hydro-Gear EZT	
Forward Speeds	0-7 mph (0-11.26 kph), infinitely variable	
Reverse Speeds	0-3.5 mph (0-5.63 kph), infinitely variable	
Steering	Twin-lever, SmoothTrak™ steering provides independent control of each drive wheel. Speed, forward, reverse, brake, and true zero-degree-radius turns are all controlled with hand-operated controls	
Brakes		
Service	Hydrostatic dynamic braking	
Parking	Sprocket and cog. When steering levers are placed in neutral position, integral park brakes are automatically engaged	
Seat	Molded vinyl seat. Fore and aft adjustment. Optional armrests. Standard seat spring	
Tires		
Front Casters	11 x 4 – 5, rib tread	
Drive Drive	36 in: 18 x 8.50 – 8, turf tread	
	42 in: 18 x 9.50 – 8, turf tread	
Dimensions		
Height	37.3 in (94.74 cm)	
W/36 in Deck	Length:	72.5 in (184.15cm)
	Overall width:	35.9 in (91.19 cm) w/discharge chute up
	Tire-to-tire width:	35.5 in (90.17cm)
	Weight:	552 lbs (250.33 kg)
W/42 in Deck	Length:	74 in (187.96 cm)
	Overall width:	41.6 in (105.66 cm) w/discharge chute up
	Tire-to-tire width:	37.75 in (95.89 cm)
	Weight:	572 lbs (259.40 kg)
Deck Lift	Raise and lower deck from driver's seat with simple foot-operated deck height adjustment. Pin for setting height, transport position. Change cutting heights, hop curbs and trailer more easily	
Cutting Heights	1.5 in to 4 in (3.81 cm to 10.16 cm) in .25 in increments	
Mowing Blades	Heavy-duty, heat-treated, high-lift steel blades	
	36 in:	1 – 20.5 in x 2.5 in x .20 in
		1 – 13.75 in x 2.5 in x .20
	42 in:	2 – 20.5 in x 2.5 in x .20 in
Blade Tip Speed	36 in:	18,200 fpm
(3550 rpm)	42 in:	18,200 fpm
Accessories	<b>Mulch Kit</b> Recycles clippings under deck allowing clippings to be cut and recut, then discharged down into the grass. Reduces handling of clippings, improves appearance, and recycles nutrients back to the soil.	

Specifications subject to change without notice.

**HUSTLER**  
Turf Equipment

For more information:

[www.hustlerturfequipment.com](http://www.hustlerturfequipment.com)

HUSTLER TURF EQUIPMENT • HESSTON, KANSAS 67062 • 1-800-395-4757