



www.billygoat.com

Product Fact Sheet

Quiet Blow® Small Frame Blowers

Markets

- Amusement Parks
- Apartment Complexes
- Campgrounds
- Cemeteries
- Colleges & Universities
- Country Clubs
- Golf Courses
- Home Owners
- Hotels & Motels
- Landscape Contractors
- Military Bases
- Municipalities
- Parks & Rec
- Paving Maintenance Contractors
- Race Tracks
- Rental Dealers
- Roofing
- Stadiums
- Utility Departments

Applications

- Leaf & Debris Removal
- Litter Removal
- Pavement Surface Preparation

Control hurricane-force winds up and down simply by squeezing and releasing the ergonomically-designed lever.

Easily converts to a powerful front-discharge blower by sliding the discharge scoop over the exhaust.

Combines light weight and the lowest noise levels in the industry for comfortable operation.



Exclusive hand-operated exhaust controls direction and timing of airstream.

Patent #6253416

Bringing Hurricane-Force Winds to the Homeowner.

The Quiet Blow® small frame wheeled blowers provide homeowners with the best control and performance at the industry's lowest noise levels by delivering the top-quality features found in the commercial mid and large frame blower lines. An ergonomically-designed lever directs airflow exactly where it is needed, right from the handle. Locking the lever in place blows leaves and debris the greatest distance with ease, while releasing the lever directs the airflow up off the working surface, eliminating over-blowing. A front discharge scoop slips on to divert airflow forward.

Specifications

Engines

5.0 hp Honda GC
6.5 hp B&S Intek I/C OHV

Weight

5.0 hp: 98 lbs. (44.5 kg)
6.5 hp: 104 lbs. (47.3 kg)

Housing

12 gauge (2.6 mm) steel
with .5" (12.7 mm) corner
radius

Handle

1" (25.4 mm) dia. x 16 gauge
(1.5 mm) steel tubing with
rubber shock mounts

Impeller

15.3" (389 mm) 14-blade glass-
filled nylon

Wheels

Rear: 10.5" (267 mm) pneumatic
ball bearing w/ turf tread
Front: 8.5" (216 mm) pneumatic
ball bearing

Noise

91 dBA to 96 dBA at operator
(Contact manufacturer for sound levels
per 2000/14/EEC)

Air Speed

Up to 167 MPH (269 km/h)

Accessories

- **Hold down kit**
(Part #430299)
- **Front caster wheel kit** (Part #430291)

For product pricing and availability, visit www.billygoat.com to find an authorized dealer near you.

© 2002 Billy Goat Industries, Inc. • P.O. Box 308 • Lee's Summit, MO 64063-0308 USA • Phone: 816/524-9666 • FAX: 816/524-6983